

**What is claimed:**

1. A power generating system, comprising:  
a ring assembly including a plurality of blades connected to a hub;  
a magnetic flux generating element coupled to the ring assembly along a  
circumference of rotation of the ring assembly;  
a current conducting element disposed on the system, which cooperates with  
the flux generating element so that relative movement induces electric  
current therein.
2. The system of claim 1 further comprising a rotary motivating mechanism  
rotatingly coupled to the hub.
3. The system of claim 1 wherein the rotary motivating mechanism is an opposed  
piston, opposed cylinder internal combustion engine.
4. The system of claim 1 wherein the engine is an opposed piston, opposed cylinder  
engine having a crankshaft.
5. The system of claim 1 wherein the blades comprise a propeller adapted to produce  
thrust propulsion for an aerial vehicle.
6. The system of claim 1 wherein the magnetic flux generating element is disposed  
on a circumferential element linking end portions of the blades.
7. The system of claim 6 wherein the circumferential element is a continuous hoop  
disposed on the ends of the blades and adapted to support a plurality of magnetic  
flux generating elements circumferentially disposed on the hoop.
8. The system of claim 7 wherein a plurality of current conducting elements are  
disposed on a stationary support included in the system.
9. The system of claim 8 wherein the magnetic flux generating elements and the  
current conducting elements are configured to provide a three-phase electrical  
power generation.

10. A ring generator comprising:  
an opposed piston, opposed cylinder engine having a crankshaft;  
a ring assembly having a shaft coupled to the crankshaft, and a magnetic flux  
5 generating element; and  
a current conducting element disposed in fixed relation to the ring assembly.
11. The ring generator of claim 10 wherein the ring assembly includes a speed  
differential apparatus disposed on the shaft and coupled to the crankshaft.
- 10 12. The ring generator of claim 10 wherein the magnetic flux generating element is a  
plurality of alternating polarity magnets.
13. The ring generator of claim 10 wherein the magnetic flux generating element  
15 comprises a circumferential element comprising a ferrous material.
14. The ring generator of claim 10 wherein the current conducting element is a stator  
assembly.
- 20 15. The ring generator of claim 14 wherein the stator assembly comprises a three-  
phase winding.
16. The ring generator of claim 14 wherein the stator assembly comprises two  
winding sets, each winding set being a three-phase winding.
- 25 17. A power generating system comprising:  
a ring assembly comprising a plurality of blades connected to a hub, and at an  
end opposite the hub the ring assembly comprises a circumferential element;  
a magnetic flux generating element coupled to the ring assembly along a  
30 circumference of rotation of the ring assembly, the magnetic flux  
generating element comprising a plurality of magnets disposed on an  
inside diameter of the circumferential element; and

a current conducting element disposed on the system, which cooperates with the flux generating element so that during relative rotating movement of the elements electric current flow is induced.

5 18. The system of claim 17 wherein the circumferential element comprises a continuous loop of ferrous material.

19. The system of claim 17 wherein the circumferential element comprises three arc segments, each segment being non contiguous.

10

20. The system of claim 17 wherein the current conducting element comprises a pair of stator assemblies.

15

21. The system of claim 20 wherein each stator assembly comprises a three-phase coil winding.